

5871 SSET

Heavy Duty Cylindrical Lock

Knob Locks



Specifications	
Material	Stainless steel
Cycle life	200,000 cycles
Chassis	Solid steel chassis and latch case, zinc plated
Trim	Zinc die-casting electro-plated or solid brass
Cylinder	5-pin tumbler, brass plug, two nickel-plated brass keys
Latch	Deadlocking on keyed functions
Handing	Fully reversible, left or right hand
Application	Commercial offices, schools and heavy-duty residential
Keying	Can be keyed alike to deadbolts
Finish	Satin stainless steel (US32D)
Function	Entrance, keyed outside

Features

- Latch Bolt: 12mm (1/2") throw with deadlocking
- Door Thickness: 35–50mm (1-3/8" to 2"), adjustable
- Backset: Standard 70mm (2-3/4"); optional 60mm or 90mm available
- Handing: Fully reversible for left or right hand doors
- Introduction
- Ideal for medium-grade commercial and heavy-duty residential applications
- Supports keyed alike function with deadbolts to enhance security
- Tested for over 200,000 life cycles

Confirm on order

Not stated in our published data, so confirm on the order: finish codes, fixing-hole positions, overall dimensions, order code per finish.

As published on [cantonlock.com](https://www.cantonlock.com). The order confirmation is the binding specification.