

607 SSBK

Tubular Lock

Knob Locks



Specifications

Material	Stainless steel/Brass/Solid steel
Cylinder	Brass cylinder
Backset	60mm / 70mm adjustable
Door thickness	35mm to 45mm adjustable
Cycle life	200,000 cycles
Chassis	Solid steel chassis and latch case, zinc plated
Trim	Wrought stainless steel or brass
Strike	57mm curved lip standard; 70mm available on request
Handing	Fully reversible, left or right hand
Application	Residential use
Finish	Satin stainless steel (US32D)
Function	Privacy, bathroom, turn button inside
Latch	Adjustable 60–70mm

Features

- Key Features:
- Latch Bolt: 12mm (1/2”) throw, deadlocking for keyed functions
- Door Thickness: Adjustable 35–45mm (1-3/8” to 1-3/4”)
- Backset: Adjustable 60mm or 70mm (2-3/8” or 2-3/4”)
- Optional Latch: 1” round drive-in 4-way latch (upon request)
- Strike Plate: 57mm curved lip standard, 70mm optional
- Handing: Reversible for left or right-hand doors

Confirm on order

Not stated in our published data, so confirm on the order: finish codes, fixing-hole positions, order code per finish.

As published on [cantonlock.com](https://www.cantonlock.com). The order confirmation is the binding specification.