

D101 DSPB

Deadbolts

Deadbolts



Specifications	
Material	Stainless steel body
Function	Single cylinder
Application	Entrance doors
Deadbolt throw	25mm, zinc die-cast with hardened steel roller insert
Cylinder	5-pin tumbler, solid brass plug, two nickel-plated brass keys
Chassis	Zinc plated steel internal components
Trim	Stainless steel, brass or steel
Handing	Fully reversible, left or right hand
Feature	Free-turning cylinder trim prevents wrenching; cylinder removable for rekeying
Keying	Can be keyed to pair with an entrance bored lock
Trim Material	Stainless steel, brass, or steel
Door thickness	Adjustable 35–45mm (1-3/8" to 1-3/4")
Backset	Adjustable 60mm or 70mm (2-3/8" or 2-3/4")

Features

- Economical and durable auxiliary deadbolt
- 25mm (1") zinc die-cast bolt with hardened steel roller insert for anti-saw protection
- Zinc-plated steel internal components
- Free-turning cylinder trim to prevent wrenching
- 5-pin solid brass cylinder, easy to rekey
- Supplied with 2 nickel-plated brass keys
- Can be keyed alike with entrance locks for enhanced exterior security

Confirm on order

Not stated in our published data, so confirm on the order: finish codes, fixing-hole positions, order code per finish.

As published on [cantonlock.com](https://www.cantonlock.com). The order confirmation is the binding specification.